



# GreenGraphics®

## Professional Permanent Turf Coating

### GENERAL DESCRIPTION

- Long Lasting
- Natural Color
- Easy to Use

GreenGraphics® Green and Green Graphics Western Special are water-based, concentrated colorant coatings intended to provide realistic green coloration in the event of drought, distress or winter dormancy. Ideal for use on grass on golf course greens, tees and fairways, sod farms, public yards, sports fields, courtyards and patios in public areas and residential yards. GreenGraphics Western Special is preferred for a more natural coloration of warm season turf. The turf colorant promotes the absorption of the sun's rays and will last until removed by mowing.

### PACKAGING

Available in 2x2.5 gallon jugs.

### DIRECTIONS FOR USE

#### Mixing Guidelines

- Stir well before using.
- Grass should be trimmed to its normal height and should be cleared of all debris (tree leaves, grass clippings, etc.).
- Mix colorant with 15 to 20 parts warm water (if possible) in a separate container and then pour into your sprayer tank. If you have an agitation device in your sprayer tank, separate mixing is not necessary.
- Prepare only the amount of material you plan to use. Any clean sprayer device which is normally used for application of chemicals is suitable for use with GreenGraphics Green, including pump-action hand held sprayers, backpack sprayers, electric sprayers and motor-powered pump and boom devices.

#### Application Equipment Guidelines

- For best results, use a flat-pattern tip with a half gallon per minute orifice. Do not paint when temperature of air is less than 40°F or surface of ground is less than 50°F.
- On very hot days, grass may be slightly dampened with water prior to painting.
- Avoid spraying on breezy days to prevent drift.
- Midday lighting is actually best as there are fewer shadows.
- Apply in even strokes, taking care to completely address one area at a time before moving on. If possible practice in a low-profile area first.
- A piece of plywood, fiberboard or cardboard may be used to prevent overspraying on foundations and walkways.
- If allowed to dry, this colorant will permanently stain concrete and other surfaces to which it might accidentally be administered. Pre-wetting of the surface and an immediate flushing and/or wiping of the surface will generally ease removal of any green color.
- Drying time is 30 minutes. Allow to cure overnight before heavy usage.
- Do not allow colorant spray solution to remain in tank and equipment overnight. Fully and completely flush tank and hose(s) with water.

### RECOMMENDED RATES

One gallon of GreenGraphics will cover approximately 4,000 to 6,000 square feet depending on height of grass, depth of color desired and method of application.

Mix Ratio <sup>1</sup>	Mix Solution Coverage <sup>2</sup>
1:15	2.6-4.0 gallons/1,000 square feet
1:20	3.5-5.25 gallons/1,000 square feet

<sup>1</sup>One part GreenGraphics Green to 15 or 20 parts water.

<sup>2</sup>Based on coverage rate of 4,000-6,000 square feet.

GreenGraphics® is a registered trademark of Becker Underwood.

